

VHF FM HANDHELD TRANSCEIVER

VX-150

144 MHz, Ultra-Rugged, 5 Watts!



Compact yet incredibly rugged, the VX-150 2-meter handheld is designed to perform under the most difficult operating conditions, and it's packed with the leading-edge features you've come to expect from a Yaesu product. The VX-150's die-cast aluminum case houses a large, high-output speaker, and the illuminated keypad provides easy viewing during nighttime operation.

- Frequency Range
 - RX 140~174 MHz
 - TX 144~148 MHz
- 5 Watts Power Output
- 209 Memories
- Direct Keypad Frequency Entry
- 7-Digit Alphanumeric Memory Labels
- CTCSS and DCS Encode/Decode
- Omni-Glow™ Display Illumination
- Two User-Definable Keypad Function Keys
- Automatic Repeater Shift (ARS)
- 9 DTMF Auto-Dial Memories (16 digits each)
- ARTS™ (Auto-Range Transponder System)
- Wide/Narrow Deviation Selection
- TX and RX Battery Savers
- Time-Out Timer (TOT)
- Smart Search™ Auto Memory Loading
- Automatic Power-Off (APO)
- MIL-STD 810D/E
- 1750 Hz Tone Calling for European Repeaters
- Busy Channel TX Lock-Out (BCLO)
- Battery Voltage Meter
- ADMS-1F PC Programmable



SPECIFICATIONS

GENERAL

Frequency Coverage: Rx 144~146 MHz (B1), 140~174 MHz (B2)
Tx 144~146 MHz (B1), (B2)
Channel Steps: 5, 10, 12.5, 15, 20, 25 & 50 kHz
Standard Repeater Shift: 600 kHz
Emission Type: G3E
Supply Voltage: 6.0 to 16.0 VDC
Current Consumption: Receive: 130 mA
Transmit (HIGH: 5 W): 1.3 A
(MID: 2 W): 800 mA
(LOW: 0.5 W): 500 mA
Auto Power Off: 8 mA
Antenna (SMA jack): YHA-62 rubber flex antenna
Case Size (WHD): 58 (W) × 108.5 (H) × 26.5 (D) mm
(2.3" × 4.3" × 1.0")
(w/o knob & antenna)
Weight (approx.): 325g w/FNB-64 & antenna

RECEIVER

Circuit Type: Double-Conversion Superheterodyne
Sensitivity (for 12 dB SINAD): Better than 0.16 µV
Adjacent Channel Selectivity: Typcal 70 dB
Intermodulation: Typcal 70 dB
Audio Output: 0.4 W @ 8 Ohms for 10 % THD @ 7.2 V

TRANSMITTER

Power Output: 5.0/2.0/0.5 W @ 7.2 V
Frequency Stability: Better than ±5 ppm
Maximum Deviation: ±5 kHz
Spurious Emissions: Better than 60 dB below Carrier
Audio Distortion (@ 1 kHz): Less than 5 % w/3 kHz Deviation
Microphone Type: 2 kΩ Condenser
Burst Tone: 1750 Hz

Specifications are subject to change, in the interest of technical improvement, without notice or obligation. Performance measurements are per EIA standards, unless noted otherwise. Comparative performance and other statements are based on market conditions as of the printing date of this brochure..

OPTIONS AND ACCESSORIES

FNB-64: 7.2 V, 700 mAh Ni-Cd Battery Pack
FNB-V57: 7.2 V, 1100 mAh Ni-Cd Battery Pack
FBA-25: Compact Dry Cell Battery Case for 6 AA-size cells
NC-72B: 120 VAC Compact Wall Charger for FNB-64
NC-72C: 240 VAC Compact Wall Charger for FNB-64
NC-72F: 220 VAC Compact Wall Charger for FNB-64
NC-73B: 120 VAC Desktop Rapid Charger
NC-73C: 240 VAC Desktop Rapid Charger
MH-34B4B: External Hand Speaker/Microphone
MH-37A4B: Earpiece/Microphone
VC-25: VOX Headset
E-DC-5B: DC Cable w/Noise Filter
E-DC-6: DC Cable; plug and wire only
CN-3: BNC-to-SMA Adapter
CT-44: Microphone Adapter
YHA-62: Rubber Flex Antenna
CT-27: Cloning Cable

Eight-key VX-110 model (w/o direct frequency and DTMF entry) also available



Availability of accessories may vary: some accessories are supplied as standard per local regulations and requirements, others may be unavailable in some regions. Check with your Yaesu dealer for additions to the abovelist. Batteries, Speaker/Mics, Chargers, etc. are warranted for one year.

About this brochure: because of printing process tolerances, the actual color hue or color density of product images shown in this brochure may be slightly different from that of the manufactured product. Some information may have been updated since the time of printing; please check with your Authorized Yaesu Dealer for complete details. Specifications guaranteed only within amateur bands.

We reserve the right to make changes at any time in equipment, optional accessories, specifications, model number, and availability.

YAESU VERTEX STANDARD CO., LTD.
4-8-8 Nakameguro, Meguro-ku, Tokyo 153-8644, Japan

For the latest Yaesu news, visit us on the Internet:
<http://www.vxstdusa.com> <http://www.yaesu.co.uk>

VERTEX STANDARD Phone 562/404-2700; Fax 562/404-1210
Email: amateursales@vxstdusa.com

US Headquarters
17210 Edwards Road, Cerritos, CA 90703, U.S.A.
International Division
8350 N.W. 52nd Terrace, Suite 201, Miami, FL 33166, U.S.A.

YAESU EUROPE B.V.
P.O. Box 75525 1118 ZN, Schiphol The Netherlands

YAESU UK LTD. Email: sales@yaesu.co.uk

Unit 12, Sun Valley Business Park, Winnall Close
Winchester, Hampshire, SO23 0LB, U.K.

VERTEX STANDARD HK LTD.
Unit 5, 20/F., Seaview Centre, 139-141 Hoi Bun Road,
Kwun Tong, Kowloon, Hong Kong